

AMBIENT OZONE CONTROLLERS

Unit	"Use With" or (Packaged With)	Misc. Specifications	Sensor Range (PPM)	Control Output Signals	Min-Max GPM	Max Pressure	Duty Cycle	12VDC, AMPS (1)	120V/60Hz, AMPS (1)	International 220V/50Hz, AMPS, Single Hot Leg (1)	Dimensions (inches) (4) (ø = Diameter)			Wt. (lbs) (4)
											H	W	D	
Ambient Ozone Controllers														
AeroQual 100	(EcoTex Laundry Systems)	Wall Mount, Power Supply Not Included	0 - 0.5 or 0 - 5.0	Volt Free			Continuous	0.4			2.50	5.125	ø	0.5
AeroQual 300		Hand Held and Wall Mount, Rechargeable Battery	0 - 0.5 or 0 - 5.0	12VDC, Volt Free, 0-5V			Continuous	0.8			7.63	4.75	2.125	1.0
AeroQual 500		Hand Held and Wall Mount, Rechargeable Battery, Data Recording	0 - 0.5 or 0 - 5.0	12VDC, Volt Free, 0-5V			Continuous	0.8			7.63	4.75	2.125	1.0
AeroQual Remote Sensor	AeroQual 300, AeroQual 500	Wall Mount, Cat 5 cable 14m Max					Continuous				2.50	5.12	ø	0.5
Dissolved Ozone Controllers														
Rosemount 1055	(HDO3-I), (HDO3-II), (HDO3-III)	Panel Mount, Probe - 1" mpt	0 - 10.0	2 - SPDT Relays 5.0 AMP Resistive, 4-20mA	15 Max	55 PSI	Continuous		0.06	0.04	6.10	6.10	3.75	3.0

NOTES:

1-The Amp rating in this section is for the product only and does not include any peripheral equipment, unless the equipment is considered built into the product

4-This is the unit size and weight only and is not the shipping size and weight. Dimensions are given in inches and decimals, weight in pounds