

ClearWater Tech Ozone

ActivTapp®

ACTIVATED OXYGEN FAUCET

*Nature's Strongest
Disinfectant at Your Fingertips*



ActivTapp - 3 Way Faucet



ActivTapp - Side Mount Faucet

ActivTapp® Faucet

ActivTapp is a new kind of residential kitchen faucet that brings nature's most powerful cleaning agent to your home. It's patented technology mixes activated oxygen with normal tap water producing a naturally safe and powerful sanitizer.

Ozone purification systems have been widely accepted in the food industry for disinfection, and give a higher level of assurance against pathogenic organisms, like *Clostridium difficile*, *E. Coli*, *Salmonella*, and *Staphylococcus Aureus*.

ActivTapp faucets reduce bacteria, pesticides, and viruses, found on fruits, vegetables, seafood, poultry, and virtually anything you rinse. This keeps food fresh, allowing them to retain their quality, color, and flavor longer. The system also disinfects and oxidizes multi-food surfaces, reducing mold and mildew.

Benefits

- Real time proof of delivery
- Improves food safety and quality control
- Produced on site, nothing to store or transport
- Can extend shelf life
- Organic and sustainable

Applications

- Fruit & vegetable rinse systems
- Surface sanitation
- Seafood processing
- Butcher blocks
- Hand wash
- Wash cloth rinse
- Food processing
- Meat processing
- Poultry processing
- Package sanitation
- Process water purification



Ozone is Approved by the FDA & USDA

ActivTapp 3-Way

This single handle, 3-way primary kitchen faucet, provides activated-oxygen (ozone) on-demand. This elegant faucet has a brushed nickel finish, and also provides traditional cold water and hot water.



Single Hole Installation

Specifications

ELECTRICAL: 120/240V 50/60Hz @ 6.0W

WATER PRESSURE: 35 to 70 PSI

FLOW RATE: 1.3 - 2.2 GPM

WATER TEMPERATURE: 39° F to 175° F

DIMENSIONS (FAUCET): 8.5" l x 16.75" h x 1.75" ø

DIMENSIONS (OZONE): 7.5" l x 5.0" h x 1.75" d

SINK HOLE DIMENSIONS: 1.5 in.

CONNECTION SIZE: 3/8 in.

Included in Package:

- Faucet
- Ozone generator with power supply
- Brushed nickel
- Hoses
- Installation hardware

ActivTapp Side-Mount Faucet

This brushed nickel finish, single handle, side mount secondary faucet, provides activated-oxygen (ozone) on-demand, allowing for use of existing faucet.



Single Hole Installation

Specifications

ELECTRICAL: 120/240V 50/60Hz @ 6.0W

WATER PRESSURE: 35 to 70 PSI

FLOW RATE: 1.5 - 2.2 GPM

WATER TEMPERATURE: 39° F to 175° F

DIMENSIONS (FAUCET): 5.0" l x 7.375" h x 2.0" ø

DIMENSIONS (OZONE): 7.5" l x 5.0" h x 1.75" d

SINK HOLE DIMENSIONS: 1.5 in.

CONNECTION SIZE: 3/8 in.

Included in Package:

- Pull out faucet
- Ozone generator with power supply
- Brushed nickel
- Hoses
- Installation hardware



KTW-DVGW



ClearWater Tech, LLC

Ozone Systems for Water and Air Purification

800-262-0203 | 850 Capitolio Way, San Luis Obispo, CA 93401 | sales@cwtozone.com | cwtozone.com