
ClearWater Tech, LLC MINI SERIES CORONA DISCHARGE OZONE SYSTEMS











RESIDENTIAL POOLS

BOTTLED WATER

AQUARIUMS

WATER FEATURES

COMMERCIAL SPAS



CD12/AD



MINI SERIES CORONA DISCHARGE OZONE SYSTEMS

The Mini Series produce more ozone using less electrical energy than any other ozone generators on the market today. With features that include compact size, fully adjustable ozone output, convenient electrical interface plug, and 4-20mA control circuitry, these units are a perfect combination of versatility, efficiency, and solid-state reliability.

FEATURES

- Compact, wall-mounted
- Powder coated enclosure
- · Air cooled for ease of installation
- Solid-state components
- Check valve assembly
- · LED display
- 4-20 mA control or manual variable
- · Available in stainless steel

BENEFITS

- Complete sanitation on contact
- · Eliminates odors
- Reduces/eliminates chemical use
 Produced on-site (no storage, mixing, or handling of chemicals)
- Ozone reduces wasterwater pollutants

MINI SERIES SPECIFICATIONS

Unit	Grams Per Hour @ SCFH		Concentration By Weight @ Rated SCFH		120V/60Hz, AMPS	220V/50Hz AMPS, Single Hot Leg	240/60Hz, AMPS	90-250V 47-63Hz, AMPS	Dimensions (inches)			Wt.
	Dry Air	Oxygen	Dry Air	Oxygen					н	w	D	lbs
CD10	1.3@4	4@4	1.0	3.0	0.80	0.70	0.70	1.1-0.70	19.0	9.00	5.00	9.50
CD10/AD	1.3@4		1.0		2.00	1.10	1.00	2.6-1.0	19.5	11.50	5.00	14.5
CD12	2.6@8	8@8	1.0	3.0	1.70	1.00	0.90	2.3-0.9	21.5	11.50	5.00	14.5
CD12/AD	2.6@8		1.0		3.20	1.60	1.60	4.2-1.6	19.5	15.25	7.50	34.0



APPLICATIONS

- Residential swimming pools
- Commercial spas
- · Residential well water
- Bottled water
- · Waste water
- Commercial laundry
- Water features
- Aquaculture
- · Surface sanitation