

PUMPS & CIRCULATION SYSTEMS

UNIT	"Use With" or Packaged With)	Misc. Specifications	Control Output Signals	Mazzei Injector Model	Inlet/Outlet Dimension (inches)	GPM @ TDH	Max Pressure	Duty Cycle	Horse Power @ Electrical Phase	120V/60Hz, AMPS (1)	120-240V, 50-60Hz, AMPS (1)	Intern. 220V/50Hz, AMPS, Single Hot Leg (1)	208-240V, 50-60Hz, AMPS (1)	208-230/460V, 50-60Hz, AMPS (1)	Dimensions (inches) (4) (ø = Diameter)			Wt. (lbs) (4)	
															H	W	D	lbs	
PUB10	Pool and Spa Pump - GPM Flow Booster pump	WhisperFlo			2.00 fpt / 2.00 fpt	50GPM @ 60TDH		Continuous	0.50HP @ 1PH		10.8-5.4					12.75	10.75	24.5	41.0
PUB15	Pool and Spa Pump - GPM Flow Booster pump	WhisperFlo			2.00 fpt / 2.00 fpt	65GPM @ 60TDH		Continuous	0.75HP @ 1PH		10.8-5.4					12.75	10.75	24.5	41.0
PUB20	Pool and Spa Pump - GPM Flow Booster pump	WhisperFlo			2.00 fpt / 2.00 fpt	80GPM @ 60TDH		Continuous	1.00HP @ 1PH		14.2-7.1					12.75	10.75	25.0	46.0
PUB22	Pool and Spa Pump - GPM Flow Booster pump	WhisperFlo			2.00 fpt / 2.00 fpt	80GPM @ 60TDH		Continuous	1.00HP @ 3PH					5.0-4.4/2.3		12.75	10.75	25.0	46.0
PUB30	Pool and Spa Pump - GPM Flow Booster pump	WhisperFlo			2.00 fpt / 2.00 fpt	105GPM @ 60TDH		Continuous	1.50HP @ 1PH				9.6-8.3		12.75	10.75	25.25	54.0	
PUB32	Pool and Spa Pump - GPM Flow Booster pump	WhisperFlo			2.00 fpt / 2.00 fpt	105GPM @ 60TDH		Continuous	1.50HP @ 3PH					6.4-5.6/2.9		12.75	10.75	25.25	54.0
PUB40	Pool and Spa Pump - GPM Flow Booster pump	WhisperFlo			2.00 fpt / 2.00 fpt	115GPM @ 60TDH		Continuous	2.00HP @ 1PH				11.0-9.6		12.75	10.75	25.75	55.0	
PUB42	Pool and Spa Pump - GPM Flow Booster pump	WhisperFlo			2.00 fpt / 2.00 fpt	115GPM @ 60TDH		Continuous	2.00HP @ 3PH					7.1-6.2/3.4		12.75	10.75	25.75	56.0
PUB50	Pool and Spa Pump - GPM Flow Booster pump	WhisperFlo			2.00 fpt / 2.00 fpt	145GPM @ 60TDH		Continuous	3.00HP @ 1PH				15.0-13.0		12.75	10.75	25.75	56.0	
PUB52	Pool and Spa Pump - GPM Flow Booster pump	WhisperFlo			2.00 fpt / 2.00 fpt	145GPM @ 60TDH		Continuous	3.00HP @ 3PH					11.0-9.6/5.2		12.75	10.75	25.75	58.0
PUP08	Multiple Applications - Pressure Booster Pump	G & L NPE Stainless Steel			1.25 fpt / 1.00 fpt	24GPM @ 40TDH	125 PSI	Continuous	0.50HP @ 1PH		6.0-3.0					8.75	8.25	15.375	47.0
PUP10	Multiple Applications - Pressure Booster Pump, (PCE10)	G & L NPE Stainless Steel			1.25 fpt / 1.00 fpt	26GPM @ 60TDH	125 PSI	Continuous	0.75HP @ 1PH		8.5-4.3					8.75	8.25	15.625	41.0
PUP20	Multiple Applications - Pressure Booster Pump, (PCE15)	G & L NPE Stainless Steel			1.25 fpt / 1.00 fpt	30GPM @ 70TDH	125 PSI	Continuous	1.00HP @ 1PH		11.2-5.6					8.75	8.25	16.375	49.0
PUP21	Multiple Applications - Pressure Booster Pump	G & L NPE Stainless Steel			1.25 fpt / 1.00 fpt	36GPM @ 100TDH	125 PSI	Continuous	2.00HP @ 1PH		20.0-10.0					8.75	8.25	17.375	60.0
PRO-10 (2)	Multiple Applications - Circulation Pump	24-hour timer control	Dry Contact, Auxiliary Power	784	0.75 barb / 0.75 barb	5GPM @ 21TDH	50 PSI	Continuous	1/15HP @ 1PH	1.0						12.5	12.75	6.0	7.25
PRO-12 (2)	Multiple Applications - Circulation Pump	24-hour timer control	Dry Contact, Auxiliary Power	784	0.75 barb / 0.75 barb	5GPM @ 21TDH	50 PSI	Continuous	1/15HP @ 1PH			0.6				12.5	12.75	6.0	7.25

NOTES:

1-The Amp rating in this section is for the product only and does not include any peripheral equipment, unless the equipment is considered built into the product

2-Auxiliary outlet not to exceed 3.0 amps

4-This is the unit size and weight only and is not the shipping size and weight. Dimensions are given in inches and decimals, weight in pounds