

VACUUM BREAK

Unit	"Use With" or (Packaged With)	Misc. Specifications	Inlet/Outlet Dimension (inches)	Dimensions (inches) (1) (ø = Diameter)			Wt. (lbs) (1)
				H	W	D	lbs
VJB150	CD10, CD10AD, CD12, M1500, CD1500, M15AD, P2000, CD2000, M15/O2, CD15/O2, P20/O2, CD20/O2, CD4000, CD4000HO, CD6000, CD6000HO, (APEX II), (APEX III), (APEX IV), (APEX V), (APEX VI), (H003-I), (H003-II)	Back Flow Prevention	0.250 kynar comp	48.000	6.500	2.000	5.00
VJB155	CD1500P, CD2000P, CD4000P, CD6000P, (H003-III)	Back Flow Prevention	0.250 s.s. comp	48.000	6.500	2.000	5.00
VJB250	CD8000, CD8000HO, CD12000, CD12000HO	Back Flow Prevention	0.500 kynar comp	48.000	6.500	2.000	5.00
VJB255	CD8000P, CD12000P	Back Flow Prevention	0.500 s.s. comp	48.000	6.500	2.000	5.00

NOTES:

1-This is the unit size and weight only and is not the shipping size and weight. Dimensions are given in inches and decimals, weight in pounds